



Front Loading dishwasher GE-500BDD

Door Clearance 320
Dimensions (mm) 600 x 600 x 820
Power (kW) 3,4
Voltage 230V-50Hz

Description

Electromechanical control panel.

- 1 washing cycle of 120".
- Tank capacity: 25 l. / Heating power: 2.8 kw.
- Boiler capacity: 7 l. / Heating power: 2.8 kw.
- Wash pump power: 0.6 kw.
- Rinsing consumption: 2.7 l/rinse.
- Upper and lower washing and rinsing arms.
- Stainless steel washing arms.
- Built-in rinse aid dispenser.
- · Anti backflow valve fitted.
- Safety thermostat in washing tank and boiler.
- Temperatures adjusted: wash 60 °C and rinse 85 °C.
- Supply voltage: 230V / 1N 50 Hz.
- Accessories supplied: 1 basket CP-16/18, 1 basket CT-10 and 1 basket for cutlery CU-7.OPTIONAL MODELS WITH –
- Built-in detergent aid dispenser.
- Built-in draining pump.
- Stainless steel filter trays.
- Stainless steel rinsing arms. –
- UK version: With 2.2 kW boiler heating power, 2 kW tank heating power and UK plug (13A).
- 60 Hz version.

Additional Information

Power: 3,4 (kW)

Product Depth: 820





106 Fairbank Rd Clayton South VIC 3169 | (03) 9551 3034 | sales@concordefe.com.au

Product Height: 600 Product Width: 600