



## Glasswasher GE-400BDD

Door Clearance 270  
Dimensions (mm) 470 x 525 x 720  
Power (kW) 3,05  
Voltage 230V-50Hz

### Description

Electromechanical control panel.

- 1 washing cycle of 120".
- Tank capacity: 15 l. / Heating power: 2.0 kw.
- Boiler capacity: 5 l. / Heating power: 2.8 kw.
- Wash pump power: 0.3 kw.
- Rinsing consumption: 2.5 l/rinse.
- Upper and lower washing and rinsing arms.
- Independent cycle for cold rinsing.
- Built-in rinse aid dispenser.
- Anti-backflow valve fitted.
- Safety thermostat in washing tank and boiler.
- Temperature adjustment: Wash 60 °C and rinse 85 °C.
- Supply voltage: 230V / 1N 50 Hz.
- Accessories supplied: 2 baskets of 400 x 400 mm, 1 dish bracket and 1 basket for cutlery CU.

### OPTIONAL MODELS WITH

- Built-in detergent aid dispenser.
- Built-in draining pump.
- Stainless steel washing and rinsing arms.
- UK version.
- With 2.4 kW boiler heating power and UK plug (13A).
- 60 Hz version.

### Additional Information

**Power :** 3,05 (kW)

**Product Depth :** 720

**Product Height :** 470

**Product Width :** 525